

30V Dual N-Channel Enhancement Mode MOSFET

Dual N-Channel Enhancement Mode

DESCRIPTION

The STN4842 is the Dual N-Channel logic enhancement mode power field effect transistor is produced using high cell density, advanced trench technology to provide excellent $R_{DS(ON)}$. This device is suitable for use as a load switch or in PWM and gate charge for most of the synchronous buck converter applications.

STN4842M-TRG ROHS Compliant This is Halogen Free

FEATURE


- ◆ **30V / 7.8A, $R_{DS(ON)} = 16m\Omega$ (typ.)@ $V_{GS} = 10V$**
- ◆ **30V / 5.8A, $R_{DS(ON)} = 24m\Omega$ (typ.)@ $V_{GS} = 4.5V$**
- ◆ Super high density cell design for extremely low $R_{DS(ON)}$
- ◆ Exceptional on-resistance and Maximum DC current capability

APPLICATIONS


- ◆ High Frequency Point-of-Load Synchronous
- ◆ Newworking DC-DC Power System
- ◆ Load Switch



PIN CONFIGURATION



SOP-8
Top View



PART NUMBER INFORMATION

<u>ST</u> <u>N</u> <u>4842</u> <u>M</u> - <u>TR</u> <u>G</u> a b c d e f	a : Company name. b : Channel type. c : Product Serial number. d : Package code e : Handling code f : Green product code
---	---

ORDERING INFORMATION

Part Number	Package Code	Handling Code	Shipping
STN4842M-TRG	M : SOP-8	TR : Tape&Reel	2.5K/Reel

※ Year Code : 00 ~ 90, 2010 : 00

※ Week Code : 01 ~ 54

※ SOP-8 : Only available in tape and reel packaging.

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C Unless otherwise noted)

Symbol	Parameter	Typical	Unit
V _{DSS}	Drain-Source Voltage	30	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Continuous Drain Current, V _{GS} =10V ^A	T _A =25°C	7.8
		T _A =70°C	6.5
I _{DM}	Pulsed Drain Current ^B	25	A
E _{AS}	Single Pulse Avalanche energy L=0.1mH ^C	27	mJ
I _{AS}	Avalanche Current	14	A
P _D	Power Dissipation	T _A =25°C	2.0
		T _A =70°C	1.4
T _J	Operation Junction Temperature	-55/150	°C
T _{STG}	Storage Temperature Range	-55/150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

THERMAL DATA

Symbol	Parameter	Min	Typ	Max	Unit
R _{θJA}	Thermal Resistance-Junction to Ambient ^A Steady-State			85	°C/W
R _{θJC}	Thermal Resistance Junction to Lead ^A Steady-State			50	°C/W

ELECTRICAL CHARACTERISTICS (T_A = 25°C Unless otherwise noted)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Parameters						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	30			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	1.0		2.5	V
I _{GSS}	Gate Leakage Current	V _{DS} = 0V, V _{GS} = ±20V			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 24V, V _{GS} = 0V T _J = 25°C			1	μA
		V _{DS} = 24V, V _{GS} = 0V T _J = 55°C			5	
R _{DS(ON)}	Drain-source On-Resistance ^B	V _{GS} = 10V, I _D = 7.8A V _{GS} = 4.5V, I _D = 5.8A		16 24	20 30	mΩ
G _{fs}	Forward Transconductance	V _{DS} = 10V, I _D = 6A		5.6		S
Source-Drain Diode						
V _{SD}	Diode Forward Voltage ^B	I _S = 1.7A, V _{GS} = 0V		0.75	1.0	V
I _S	Continuous Source Current ^{AD}				5.8	A
Dynamic Parameters						
Q _g (4.5V)	Total Gate Charge	V _{DS} = 15V, V _{GS} = 4.5V I _D = 5.8A		5	7.2	nC
Q _{gs}	Gate-Source Charge			1.6		
Q _{gd}	Gate-Drain Charge			1.9		
C _{iss}	Input Capacitance	V _{DS} = 15V, V _{GS} = 0V f = 1MHz		420	586	pF
C _{oss}	Output Capacitance			65		
C _{rss}	Reverse Transfer Capacitance			52		
t _{d(on)}	Turn-On Time	V _{DD} = 15V, V _{GEN} = 10V, R _G = 3.3Ω,		2.2	4.4	nS
t _r				38.7	68.8	
t _{d(off)}	Turn-Off Time			12.5	25	
t _f				4.8	9.6	







Note:

- The value of R_{θJA} is measured with the device mounted on 1in 2 FR-4 board with 2oz. Copper, in a still air environment with T_A = 25°C.
- The data tested by pulsed, pulse width ≤ 300μs, duty cycle ≤ 2%
- The EAS data shows Max. rating. The test condition is V_{DD} = 25V, V_{GS} = 10V, L = 0.1mH.
- The data is theoretically the same as I_D and I_{DM}, in real applications, should be limited by total power dissipation.






The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date

We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.

TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS



SOP-8 PACKAGE DIMENSIONS

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.040	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 BSC		0.050 BSC	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

