

Single N-Channel MOSFET

DESCRIPTION

SMC2334 is the N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced trench technology devices are well suited for high efficiency fast switching applications, low in-line power loss are needed in small outline surface mount package.

PART NUMBER INFORMATION

SMC 2334 SN - TR G
 a b c d e

- a : Company name.
- b : Product Serial number.
- c : Package code SN: SOT-23
- d : Handling code TR: Tape&Reel
- e : Green produce code G: *RoHS Compliant*

FEATURES


$V_{DS} = 20V, I_D = 5.7A$

$R_{DS(ON)}=22m\Omega(Typ.)@V_{GS}=4.5V$
 $R_{DS(ON)}=25m\Omega(Typ.)@V_{GS}=2.5V$
 $R_{DS(ON)}=30m\Omega(Typ.)@V_{GS}=1.8V$


- ◆ Fast switch
- ◆ 1.8V Low gate drive applications
- ◆ High power and current handling capability

APPLICATIONS

- ◆ Hand-Held Instruments
- ◆ Load Switch



SOT-23



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ Unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-Source Voltage	20	V
V_{GSS}	Gate-Source Voltage	± 12	V
I_D	Continuous Drain Current	$T_A=25^\circ C$	5.7
		$T_A=70^\circ C$	4.6
I_{DM}	Pulsed Drain Current ^A	22	A
P_D	Power Dissipation ^C	$T_A=25^\circ C$	1.3
		$T_A=70^\circ C$	0.8
T_J	Operation Junction Temperature	-55/150	$^\circ C$
T_{STG}	Storage Temperature Range	-55/150	$^\circ C$

THERMAL RESISTANCE

Symbol	Parameter	Typ	Max	Units
$R_{\theta JA}$	Thermal Resistance Junction to Ambient ^B	$t \leq 10s$	95	$^\circ C/W$
	Thermal Resistance Junction to Ambient ^{BD}	Steady-State	130	

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)







Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Parameters						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250 μ A	20			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250 μ A	0.4	0.7	1	V
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} = \pm 12V			\pm 100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =20V, V _{GS} =0V, T _J =25 $^\circ$ C			1	μ A
		V _{DS} =16V, V _{GS} =0V, T _J =75 $^\circ$ C			10	
R _{DS(ON)}	Drain-source On-Resistance	V _{GS} =4.5V, I _D =5.7A		22	26	m Ω
		V _{GS} =2.5V, I _D =4A		25	29	
		V _{GS} =1.8V, I _D =3A		30	38	
G _{fs}	Forward Transconductance	V _{DS} =5V, I _D =3A		6		S
Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _S =1A, V _{GS} =0V		0.7	1	V
I _S	Continuous Source Current				2.9	A
Dynamic and Switching Parameters						
Q _g	Total Gate Charge	V _{DS} =10V, V _{GS} =4.5V, I _D =5.7A		6	8.1	nC
Q _{gs}	Gate-Source Charge			1.78	2.4	
Q _{gd}	Gate-Drain Charge			1.6	2.2	
C _{iss}	Input Capacitance	V _{DS} =10V, V _{GS} =0V, f=1MHz		485	679	pF
C _{oss}	Output Capacitance			60	84	
C _{rss}	Reverse Transfer Capacitance			36	50	
t _{d(on)}	Turn-On Time	V _{DD} =10V, V _{GEN} =4.5V, R _G =3 Ω , I _D =1A		5		nS
t _r				4.2		
t _{d(off)}	Turn-Off Time			15		
t _f				6		

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.


- A. Pulsed width limited by maximum junction temperature, T_{J(MAX)}=150 $^\circ$ C.
- B. The value is measured with the device mounted on 1in2 FR-4 board in a still air environment T_A =25 $^\circ$ C with.
- C. The T_{J(MAX)}=150 $^\circ$ C, using junction-to-ambient thermal resistance.
- D. T_{J(MAX)}=150 $^\circ$ C, using junction-to-case thermal resistance (R_{θJC}) is more useful in additional heat sinking is used.

The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.


TYPICAL CHARACTERISTICS




TYPICAL CHARACTERISTICS




$R_{DS(ON)}$ vs Junction Temperature




Drain Current vs T_j




Maximum Safe Operation Area



Thermal Transient Impedance




Gate Charge Waveform



Switching Time Waveform

■ SOT-23 PACKAGE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°