

Single P-Channel MOSFET

DESCRIPTION

SMC3323 is the P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced trench technology devices are well suited for high efficiency fast switching applications, low in-line power loss needed in small outline surface mount package.

PART NUMBER INFORMATION

SMC 3323 SN - TR G
 a b c d e

- a : Company name.
- b : Product Serial number.
- c : Package code SN: SOT-23
- d : Handling code TR: Tape&Reel
- e : Green produce code G: *RoHS Compliant*

FEATURES


$V_{DS} = -30V$, $I_D = -4.1A$

$R_{DS(ON)}=44m\Omega(Typ.)@V_{GS}=-10V$
 $R_{DS(ON)}=50m\Omega(Typ.)@V_{GS}=-4.5V$
 $R_{DS(ON)}=65m\Omega(Typ.)@V_{GS}=-2.5V$


- ◆ Fast switch
- ◆ 2.5V Low gate drive applications

APPLICATIONS

- ◆ Portable Equipment
- ◆ Power Management



SOT-23



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ Unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-Source Voltage	-30	V
V_{GSS}	Gate-Source Voltage	± 12	V
I_D	Continuous Drain Current	$T_A=25^\circ C$	-4.1
		$T_A=70^\circ C$	-3.3
I_{DM}	Pulsed Drain Current ^A	-16.4	A
P_D	Power Dissipation ^C	$T_A=25^\circ C$	1.3
		$T_A=70^\circ C$	0.8
T_J	Operation Junction Temperature	-55/150	$^\circ C$
T_{STG}	Storage Temperature Range	-55/150	$^\circ C$

THERMAL RESISTANCE

Symbol	Parameter	Typ	Max	Units
$R_{\theta JA}$	Thermal Resistance Junction to Ambient ^B	$t \leq 10s$	95	$^\circ C/W$
	Thermal Resistance Junction to Ambient ^{BC}	Steady-State	130	

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)







Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Parameters						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250 μ A	-30			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250 μ A	-0.5	-0.7	-1	V
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} = \pm 12V			\pm 100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-30V, V _{GS} =0V, T _J =25 $^\circ$ C			-1	μ A
		V _{DS} =-24V, V _{GS} =0V, T _J =75 $^\circ$ C			-10	
R _{DS(ON)}	Drain-source On-Resistance	V _{GS} =-10V, I _D =-4.1A		44	48	m Ω
		V _{GS} =-4.5V, I _D =-3.3A		50	58	
		V _{GS} =-2.5V, I _D =-2.2A		65	78	
G _{fs}	Forward Transconductance	V _{DS} =-10V, I _D =-4.1A		16		S
Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _S =-1A, V _{GS} =0V		-0.7	-1	V
I _S	Continuous Source Current				-2.1	A
Dynamic and Switching Parameters						
Q _g (10V)	Total Gate Charge	V _{DS} =-15V, V _{GS} =-4.5V I _D =-4.1A		21.5	30	nC
Q _g (4.5V)	Total Gate Charge			10.5	14.7	
Q _{gs}	Gate-Source Charge			1.75	2.5	
Q _{gd}	Gate-Drain Charge			2.9	4.1	
C _{iss}	Input Capacitance	V _{DS} =-15V, V _{GS} =0V, f=1MHz		860		pF
C _{oss}	Output Capacitance			92		
C _{rss}	Reverse Transfer Capacitance			55		
t _{d(on)}	Turn-On Time	V _{DD} =-15V, V _{GEN} =-10V, R _G =3 Ω , I _D =-1A		6.2	12	nS
t _r				11.3	21	
t _{d(off)}	Turn-Off Time			38	72	
t _f				12	23	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.







- Pulsed width limited by maximum junction temperature, T_{J(MAX)}=150 $^\circ$ C.
- The value is measured with the device mounted on 1in2 FR-4 board in a still air environment T_A =25 $^\circ$ C with.
- The T_{J(MAX)}=150 $^\circ$ C, using junction-to-ambient thermal resistance.
- T_{J(MAX)}=150 $^\circ$ C, using junction-to-case thermal resistance (R_{θJC}) is more useful in additional heat sinking is used.

The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.


TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS



■ SOT-23 PACKAGE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°