

### DESCRIPTION

SMC6276ESD6 used trench technology are well suited for high efficiency fast switching applications, this MOSFET has been designed to minimize the on-state resistance and yet maintain superior switching performance, this devices are well suited for applications in the small surface mount package.

### PART NUMBER INFORMATION

**SMC 6276 E SD6 - TR G**  
 a b c d e f

- a : Company name
- b : Product Serial number
- c : ESD Protection
- d : Package code SD6: SOT-363
- e : Handling code TR: Tape&Reel
- f : Green produce code G: RoHS Compliant

### FEATURES


**$V_{DS}=60V, I_D=0.29A$**

$R_{DS(ON)}=1.5\Omega(Typ.)@V_{GS}=10V$   
 $R_{DS(ON)}=2.0\Omega(Typ.)@V_{GS}=4.5V$

- ◆ High Speed Switching
- ◆ ESD Protection  $>\pm 2KV$  HBM

### APPLICATIONS

- ◆ Portable appliances
- ◆ Analog switching application.



### ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ C$ Unless otherwise noted )

Symbol	Parameter	Rating	Units	
$V_{DSS}$	Drain-Source Voltage	60	V	
$V_{GSS}$	Gate-Source Voltage	$\pm 20$	V	
$I_D$	Continuous Drain Current	$T_A=25^\circ C$	0.29	A
		$T_A=70^\circ C$	0.23	A
$I_{DM}$	Pulsed Drain Current <sup>B</sup>	1	A	
$P_D$	Power Dissipation <sup>A</sup>	$T_A=25^\circ C$	0.26	W
		$T_A=70^\circ C$	0.17	W
$T_J$	Operation Junction Temperature	-55/150	$^\circ C$	
$T_{STG}$	Storage Temperature Range	-55/150	$^\circ C$	

### THERMAL RESISTANCE

Symbol	Parameter	Typ	Max	Units
$R_{\theta JA}$	Thermal Resistance Junction to Ambient <sup>A</sup>	$t \leq 10s$	-	$^\circ C/W$
	Thermal Resistance Junction to Ambient <sup>AC</sup>	Steady-State	480	$^\circ C/W$

## ELECTRICAL CHARACTERISTICS ( $T_A=25^\circ\text{C}$ Unless otherwise noted)


Symbol	Parameter	Condition	Min	Typ	Max	Unit
<b>Static Parameters</b>						
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	60			V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	1	1.6	2.5	V
I <sub>GSS</sub>	Gate Leakage Current	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V			±10	μA
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =20V, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C			1	μA
		V <sub>DS</sub> =12V, V <sub>GS</sub> =0V, T <sub>J</sub> =85°C			30	
R <sub>DS(ON)</sub>	Drain-source On-Resistance <sup>D</sup>	V <sub>GS</sub> =10V, I <sub>D</sub> =0.26A		1.5	1.8	Ω
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =0.2A		2	2.5	
<b>Diode Characteristics</b>						
V <sub>SD</sub>	Diode Forward Voltage <sup>D</sup>	I <sub>S</sub> =0.2A, V <sub>GS</sub> =0V			1	V
I <sub>S</sub>	Diode Continuous Forward Current				0.15	A
t <sub>rr</sub>	Reverse Recovery Time	I <sub>S</sub> =0.4A, di/dt=100A/μs		40		ns
Q <sub>rr</sub>	Reverse Recovery Charge			39		nC
<b>Dynamic and Switching Parameters <sup>E</sup></b>						
Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> =15V, V <sub>GS</sub> =10V I <sub>D</sub> =0.4A		0.65		nC
Q <sub>gs</sub>	Gate-Source Charge			0.1		
Q <sub>gd</sub>	Gate-Drain Charge			0.21		
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =25V, V <sub>GS</sub> =0V, f=1MHz		31		pF
C <sub>oss</sub>	Output Capacitance			4.2		
C <sub>rss</sub>	Reverse Transfer Capacitance			3		
t <sub>d(on)</sub>	Turn-On Time		V <sub>DD</sub> =30V, V <sub>GS</sub> =10V, R <sub>G</sub> =25Ω, I <sub>D</sub> =0.4		3.8	
t <sub>r</sub>				3.6	6.8	
t <sub>d(off)</sub>	Turn-Off Time			16	30	
t <sub>f</sub>				10	19	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.


- A. Surface mounted on FR4 board using the minimum recommended pad size.
- B. Pulsed width limited by maximum junction temperature, T<sub>J(MAX)</sub>=150°C.
- C. Using ≤ 10s junction-to-ambient thermal resistance is base on T<sub>J(MAX)</sub>=150°C.
- D. Pulse test width ≤300μs and duty cycle ≤ 2%.
- E. Guaranteed by design, not subject to production testing.

The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.


## TYPICAL CHARACTERISTICS




**Output Characteristics**




**Drain-Source On Resistance**




**Gate Charge**



**Capacitance**









**Gate Threshold Voltage**




**Power Dissipation**


## TYPICAL CHARACTERISTICS



## ■ SOT-363 PACKAGE DIMENSIONS



Recommended Land Pattern



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.100	0.035	0.043
A1	0.800	1.000	0.031	0.039
b	0.150	0.350	0.006	0.014
c	0.100	0.250	0.004	0.010
D	1.800	2.200	0.071	0.087
E	1.150	1.350	0.045	0.053
E1	2.000	2.400	0.079	0.094
e	0.650 BSC.		0.026 BSC.	
e1	1.200	1.400	0.047	0.055
L	0.100	0.350	0.004	0.014
theta	0°	8°	0°	8°